



中国船级社  
CHINA CLASSIFICATION SOCIETY

证书格式号/Form: T01.01-  
HQ000049

型式认可证书  
CERTIFICATE OF TYPE APPROVAL

证书编号/Certificate No. NY08T00004

兹证明本证书所述制造厂生产的下列产品能够满足下面列明认可标准的要求。

This is to certify that the following products produced by the manufacturer stated in the certificate can meet the requirements of the approval standards listed below.

认可产品/Product Approved

NoSpray Protection System Tapes and Sheets (IM2002)

NoSpray Protection System Tapes and Sheets (IM2002)

密封材料

制造厂/Manufacturer

Nospray Protection System Ltd.

Nospray Protection System Ltd.

861 Derwent Way, Delta, British Columbia V3M5R4, Canada

861 Derwent Way, Delta, British Columbia V3M5R4, Canada

认可标准/Approval Standard

证书有效期至/ This Certificate is valid until

2012年5月29日 / May. 29, 2012

发证机构  
Issued by 中国船级社纽约办事处  
CCS New York Office

签发日期  
Date 2008年5月30日  
May. 30, 2008

本证书根据中国船级社《国际船舶入级规范》及有关程序制定颁发。关于证书的有关规定见本证书背面的说明。当本证书包括多页时，因所有证书为一个整体，必须同时使用。每页证书均由本社盖章方为有效。证书复印件无效。任何单位和个人均不得涂改或节选本证书的部分内容。本认可证书不代表本社对个体产品质量的检验。有关各方对所持证书的真实性负责。如有任何疑问，可向本社技术机构咨询。  
This Certificate is issued pursuant to the Rules for Classification of Sea-going Steel Ships and related procedures of the Society. Refer to the back of the certificate for detailed requirements of the certificate. When the certificate consists of more than one page, all pages of the certificate are taken as a whole and are used simultaneously. No certificate page is valid without bearing the stamp of the Society and no copied form of the certificate is regarded as valid. Any part of the certificate is not to be extracted or abridged by any unit or individual in any form. This approval certificate does not constitute the inspection of the Society about the quality of the unit/batch product. Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices.



NY15606866

中国船级社总部/CCS headquarters: 北京东直门南大街9号船检大厦 邮编: 100007 电话/Tel: +86(10)58112288 传真/Fax: +86(10)58112811  
CCS Mansion, 9 Dongzhimen Nan Da Jie, Beijing 100007, China 网址/Web Site: <http://www.ccs.org.cn>

本地检验机构/CCS Local Office: 中国船级社纽约办事处 CCS New York Office 电话/Tel: 1(516)396-7368 传真/Fax: 1(516)396-7369

**产品明细/ Product Description**

密封材料

产品型号/Model : No-spray tape & sheet(IM2002)  
 规格/Specification : See "Others" for details. mm  
 材料/Material : Aluminium/glass cloth jacketing system with one side coated with a silicon adhesive for installation.

**批准的图纸和设计计算书/ Approved Drawings and Design Calculations**

图纸批准号/ Drawings Approval No. :

**产品认可试验报告/ Approval Test Report**

试验报告编号/Test Report No. : 410-1-5166-GDR1  
 试验报告日期/Test Report Date: : 2003-01-22  
 试验单位/ Laboratory: : -  
 试验单位地址/ Test Address: : DNV Survey Report for Surface Flammability Tests of "NoSpray Protection System Metallic Tape"  
 : -  
 试验报告编号/Test Report No. : Fire Performance of "NoSpray Protection System"  
 试验报告日期/Test Report Date: : 2003-01-23  
 试验单位/ Laboratory: : -  
 试验单位地址/ Test Address: : Southwest Research Institute  
 : -  
 试验报告编号/Test Report No. : Project 03-117  
 试验报告日期/Test Report Date: : 2003-01-27  
 试验单位/ Laboratory: : -  
 试验单位地址/ Test Address: : Chemsultants, Test Report for Peel Adhesion, Release, Tensile and Elongation, Total Caliper  
 : -  
 试验报告编号/Test Report No. : CMC02/032  
 试验报告日期/Test Report Date: : 2003-02-25  
 试验单位/ Laboratory: : -  
 试验单位地址/ Test Address: : DNV Report for Witness Leakage Test of "NoSpray Tape or Sheet"  
 : -  
 : -

**产品适用范围/Application of the Product**


For screening of pipe joints and fittings in system for fuel oil, lub. oil and other flammable oils to prevent oil spray onto the source of ignition required by Reg. 4.2.5.4, 4.6.4.3 of Chapter 4, Part III of CCS Rules (2006) and Reg. 4.2.2.5.3 of Ch. II-2, SOLAS Consolidated Edition 2004.

Approval Conditions:

1. For use on pipes and joints of :  
 Max. Temperature: 150°C; Max. Pressure: 2.0MPa;  
 Nominal Pipe Dia.: Up to 50mm for screwed joints and 300mm for flanged joints.
2. Restricted to oil pressure pipes located above the floor plates and which have no insulation in way of the joints. Use is also restricted to readily accessible positions where the integrity of the application may be inspected regularly and new covering will be applied after removal for maintenance purposes.
3. The NoSpray tapes and sheets are to be installed according to the manufacturer's instructions;
4. The NoSpray Protection System can not be used for pipes insulation, or as replacement for pipe gaskets and sealings.

**认可保持条件/ Maintenance Requirements of Approval**

1. 型式认可后, 如果产品及其重要零部件的设计、所用材料或制造方法有所改变, 且影响到产品的主要特性、特征; 或产品的性能指标有所更改, 且超过认可的范围, 则有关图纸和文件应经检验机构审批。并在检验机构认为必要时, 经本社检验人员见证有关试验和进行检查, 其结果应能证实仍符合认可条件。  
 After type approval, if there are changes to the design, materials used or manufacturing method of the product and important components and such changes affect major characteristics and properties of the product, or property indexes of the product are changed and exceed the scope of approval, related drawings and documents are to be examined and approved by the concerned survey office. Where deemed necessary by the survey office, the surveyor to the Society will go to witness relevant tests and conduct inspection and the results should be able to demonstrate compliance with the approval conditions.
2. 工厂的专业质量管理体系应保持有效运行, 并且与认可时一致。如果质量管理体系发生改变, 应经原体系认证机构审核并获本社批准。  
 The professional quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.



证书编号/Certificate No. NY08T00004

3. 认可证书有效期内, 如果出现可能导致本社取消认可的情况, 工厂应及时采取有效的纠正措施。  
Within the validity of the approval certificate, if cases occur that may cause the Society to withdraw the approval, the manufacturer should take corrective actions in a prompt and effective manner.

4. 在认可证书有效期内, 本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核, 以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。  
Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

**认可后的产品检验方式/ Method of product inspection after approval**

按照规范只认可不进行产品检验的产品/The product approved only in term of the rules:

认可后的产品检验由制造厂按本社批准的产品检验计划进行检验, 经检验合格后由制造厂签发合格证明, 并连同该产品的本社认可证书复印件一并交付用户, 制造厂对产品符合公约、法规、本社规范和本社认可的标准规定负责。  
After approval, product inspection should be carried out by the Manufacturer in accordance with the product inspection scheme approved by the Society. Upon satisfactory inspection, and the Quality Certificate issued by the Manufacturer should be provided to the purchaser together with the copy of the approval certificate issued by the Society. The manufacturer should take responsibility for the product being in compliance with the convention, statutory regulation, the Society rules and the standard accepted by the Society.

**对于原材料和零部件的检验要求/ Inspection requirements for materials and components**

**责任声明/Statement of responsibility**

本认可不影响, 替代与本社授权或检验无关的各方对上述工厂的认可与发证, 并且不对与本社授权或检验无关的各方负责, 不承担其未经本社应允而承认、接受本社认可所导致的法律与经济责任。  
This approval does not affect and replace any approval and certification of the manufacturer by any parties that bear no relation with this Society's authorization or survey. This Society performs survey and approval of products according to its own rules and survey requirements, and is not liable to any parties that bear no relation with this Society's authorization or survey. The Society does not undertake any legal and economic liabilities arising from accepting this Society's certificate without prior permission from this Society.

**其他/Others**

1. 本证书由原证书换证/This type approval certificate is issued on the basis of renewal audit of the original certificate No. NY04510009.
2. Description of NoSpray Tape & Sheets:  
35mm Width x 10m Length; 50mm Width x 10m Length; 100mm Width x 10m Length; 140mm Width x 10m Length; 250mm Width x 10m Length; 500mm Width x 10m Length; 1000mm Width x 10m Length.  
Total thickness 9.5mil for all size.
3. Standard for approval:  
IMO Resolution A.653(16)  
Reg. 4.2.5.4, 4.6.4.3 of Chapter 4, Part III of CCS Rules(2006)  
Reg. 4.2.2.5.3 of Ch. II-2, SOLAS Consolidated Edition 2004

中国船级社纽约办事处

CCS New York Office



\*\*\*\*\*本证书正文完/ End of Text\*\*\*\*\*